





































CASEMENT

4 Wide Operator/Stationary Units

MO (mm)	5-4 1/2 (1638)	6-8 1/2 (2045)	8-0 1/2 (2451)	9-4 1/2 (2858)
RO (mm)	5-5 (1651)	6-9 (2057)	8-1 (2464)	9-5 (2870)
FS (mm)	5-4 (1626)	6-8 (2032)	8-0 (2438)	9-4 (2845)
2-7 3/8 (797) 2-7 5/8 (803) 2-7 1/8 (791)	 ICA17314W	 ICA21314W	 ICA25314W	 ICA29314W
2-11 3/8 (898) 2-11 5/8 (905) 2-11 1/8 (892)	 ICA1735 4W	 ICA2135 4W	 ICA2535 4W	 ICA2935 4W
3-3 3/8 (1000) 3-3 5/8 (1006) 3-3 1/8 (994)	 ICA1739 4W	 ICA2139 4W	 ICA2539 4W	 ICA2939 4W
3-7 1/2 (1105) 3-7 3/4 (1111) 3-7 1/4 (1099)	 ICA1743 4W	 ICA2143 4W	 ICA2543 4W	 ICA2943 4W E
3-11 3/8 (1203) 3-11 5/8 (1210) 3-11 1/8 (1197)	 ICA1747 4W	 ICA2147 4W	 ICA2547 4W	 ICA2947 4W E
4-7 3/8 (1406) 4-7 5/8 (1413) 4-7 1/8 (1400)	 ICA1755 4W	 ICA2155 4W	 ICA2555 4W	 ICA2955 4W E
4-11 3/8 (1508) 4-11 5/8 (1514) 4-11 1/8 (1502)	 ICA1759 4W	 ICA2159 4W	 ICA2559 4W	 ICA2959 4W E
5-3 3/8 (1610) 5-3 5/8 (1616) 5-3 1/8 (1603)	 ICA1763 4W	 ICA2163 4W	 ICA2563 4W	 ICA2963 4W E
5-11 3/8 (1813) 5-11 5/8 (1819) 5-11 1/8 (1807)	 ICA1771 4W T	 ICA2171 4W T	 ICA2571 4W T	 ICA2971 4W ET

Details and Elevations not to scale.

Special sized units available within product size matrix. See your Integrity® retailer.

E = These windows meet National Egress Codes for fire evacuation. Local codes may differ.

T = Standard Tempered

Any unit in these combinations can be operating or stationary. Operating sash are viewed from the exterior.

MULTIPLE ASSEMBLIES

Multiple assemblies can be factory mullled.

MAXIMUM ROUGH OPENING not to exceed 113" x 71 5/8" Maximum up to 7 units wide by 1 unit high.

MAXIMUM ROUGH OPENING not to exceed 85" x 94 3/4" Maximum up to 4 units wide by 5 units high.

Field mull kits are available. Structural mullion reinforcement is required for some assemblies.

Please consult your local Integrity from Marvin® representative for more information.