



CASEMENT ROUND TOP

RT6 EYEBROW ABOVE SPRINGLINE STANDARD SIZES - OPERATOR AND STATIONARY

RO (mm)	1 - 5 (432)	1 - 7 (483)	1 - 9 (533)	2 - 1 (635)	2 - 3 (686)	2 - 5 (737)	2 - 7 (787)	2 - 9 (838)	3 - 1 (940)
2 - 7 5/8 (603)	 UCART1632	 UCART1832	 UCART2032						
2 - 11 5/8 (905)	 UCART1636	 UCART1836	 UCART2036	 UCART2436					
3 - 3 5/8 (1006)	 UCART1640	 UCART1840	 UCART2040	 UCART2440	 UCART2640	 UCART2840			
3 - 7 5/8 (1108)	 UCART1644	 UCART1844	 UCART2044	 UCART2444	 UCART2644	 UCART2844 E	 UCART3044 E		
3 - 11 5/8 (1210)	 UCART1648	 UCART1848	 UCART2048	 UCART2448	 UCART2648 E	 UCART2848 E	 UCART3048 E	 UCART3248 E	
4 - 5 5/8 (1362)	 UCART1654	 UCART1854	 UCART2054	 UCART2454	 UCART2654 E	 UCART2854 E	 UCART3054 E	 UCART3254 E	 UCART3654 E

CASEMENT ROUND TOP

RT6 EYEBROW ABOVE SPRINGLINE STANDARD SIZES - OPERATOR AND STATIONARY

RO (mm)	1 - 5 (432)	1 - 7 (483)	1 - 9 (533)	2 - 1 (635)	2 - 3 (686)	2 - 5 (737)	2 - 7 (787)	2 - 9 (838)	3 - 1 (940)	3 - 5 (1041)
4 - 7 5/8 (1413)	 UCART1656	 UCART1856	 UCART2056	 UCART2456	 UCART2656 E	 UCART2856 E	 UCART3056 E	 UCART3256 E	 UCART3656 E	
4 - 11 5/8 (1514)	 UCART1660	 UCART1860	 UCART2060	 UCART2460	 UCART2660 E	 UCART2860 E	 UCART3060 E	 UCART3260 E	 UCART3660 E	 UCART4060 E
5 - 3 5/8 (1616)	 UCART1664	 UCART1864	 UCART2064	 UCART2464	 UCART2664 E	 UCART2864 E	 UCART3064 E	 UCART3264 E	 UCART3664 E	 UCART4064 E
5 - 11 5/8 (1819)	 UCART1672 T	 UCART1872 T	 UCART2072 T	 UCART2472 T	 UCART2672 T	 UCART2872 T	 UCART3072 T	 UCART3272 T	 UCART3672 T	 UCART4072 T
6 - 5 5/8 (1972)	 UCART1678 T	 UCART1878 T	 UCART2078 T	 UCART2478 T	 UCART2678 T	 UCART2878 T	 UCART3078 T	 UCART3278 T	 UCART3678 T	 UCART4078 T

Details and Elevations not to scale.

- Marvin exclusive wash mode is not available on Ultimate Casement Round Tops.

E These windows meet national Egress codes for fire evacuation. Local codes may differ.

T For safety and/or code requirements, Marvin recommends tempered glass in all units with a frame size height of 71 1/8" or larger and units with basic frame size 25.2 ft².

Please consult your local Marvin representative for more information.

For further details and drawings visit the 'Tools and Documents' section at Marvin.com.

CASEMENT ROUND TOP

RT6 EYEBROW ABOVE SPRINGLINE STANDARD SIZES - OPERATOR AND STATIONARY

RO (mm)	1 - 5 (432)	1 - 7 (483)	1 - 9 (533)	2 - 1 (635)	2 - 3 (686)	2 - 5 (737)	2 - 7 (787)	2 - 9 (838)	3 - 1 (940)	3 - 5 (1041)
6 - 11 5/8 (2124)										
	UCART1684 T	UCART1884 T	UCART2084 T	UCART2484 T	UCART2684 T	UCART2884 T	UCART3084 T	UCART3284 T	UCART3684 T	UCART4084 T
7 - 7 5/8 (2327)										
	UCART1692 T	UCART1892 T	UCART2092 T	UCART2492 T	UCART2692 T	UCART2892 T	UCART3092 T	UCART3292 T	UCART3692 T	UCART4092 T
7 - 11 5/8 (2429)										
	UCART1696 T	UCART1896 T	UCART2096 T	UCART2496 T	UCART2696 T	UCART2896 T	UCART3096 T	UCART3296 T	UCART3696 T	

Details and Elevations not to scale.

- Marvin exclusive wash mode is not available on Ultimate Casement Round Tops.
- Rough opening height includes ¹⁵/₁₆" subsill.

T For safety and/or code requirements, Marvin recommends tempered glass in all units with a frame size height of 71 ¹/₈" or larger and units with basic frame size 25.2 ft².

E These windows meet national Egress codes for fire evacuation. Local codes may differ.

Please consult your local Marvin representative for more information.

For further details and drawings visit the 'Tools and Documents' section at Marvin.com.





CASEMENT ROUND TOP

RT21 / RT22 TWO WIDE STANDARD SIZES - OPERATOR AND STATIONARY

RO (mm)	2-9 (838)	3-1 (940)	3-5 (1041)	4-1 (1245)	4-5 (1346)	4-9 (1448)
2-7 5/8 (803)	 UCART1632					
2-11 5/8 (905)	 UCART1636	 UCART1836	 UCART2036			
3-3 5/8 (1006)	 UCART1640	 UCART1840	 UCART2040	 UCART2440		
3-7 5/8 (1108)	 UCART1644	 UCART1844	 UCART2044	 UCART2444		 UCART2844
3-11 5/8 (1210)	 UCART1648	 UCART1848	 UCART2048	 UCART2448	 UCART2648	 UCART2848 E
4-5 5/8 (1362)	 UCART1654	 UCART1854	 UCART2054	 UCART2454	 UCART2654	 UCART2854 E
4-7 5/8 (1413)	 UCART1656	 UCART1856	 UCART2056	 UCART2456	 UCART2656	 UCART2856 E
4-11 5/8 (1514)	 UCART1660	 UCART1860	 UCART2060	 UCART2460	 UCART2660	 UCART2860 E

CASEMENT ROUND TOP

RT21 / RT22 TWO WIDE STANDARD SIZES - OPERATOR AND STATIONARY

RO (mm)	5-1 (1549)	5-5 (1651)	6-1 (1854)
3-11 5/8 (1210)	 UCART3048 E		
4-5 5/8 (1362)	 UCART3054 E	 UCART3254 E	
4-7 5/8 (1413)	 UCART3056 E	 UCART3256 E	 UCART3656 E
4-11 5/8 (1514)	 UCART3060 E	 UCART3260 E	 UCART3660 E

Details and Elevations not to scale.

- Marvin exclusive wash mode is not available on Ultimate Casement Round Tops.
- Rough opening height includes 15/16" subsill.

































E These windows meet national Egress codes for fire evacuation. Local codes may differ.

T For safety and/or code requirements, Marvin recommends tempered glass in all units with a frame size height of 71 1/8" or larger and units with basic frame size 25.2 ft². Please consult your local Marvin representative for more information.

For further details and drawings visit the 'Tools and Documents' section at Marvin.com.
























CASEMENT ROUND TOP

RT21 / RT22 TWO WIDE STANDARD SIZES - OPERATOR AND STATIONARY

RO (mm)	2-9 (838)	3-1 (940)	3-5 (1041)	4-1 (1245)	4-5 (1346)	4-9 (1448)
5-3 5/8 (1616)	 UCART1664	 UCART1864	 UCART2064	 UCART2464	 UCART2664	 UCART2864 E
5-11 5/8 (1819)	 UCART1672 T	 UCART1872 T	 UCART2072 T	 UCART2472 T	 UCART2672 T	 UCART2872 T
6-5 5/8 (1972)	 UCART1678 T	 UCART1878 T	 UCART2078 T	 UCART2478 T	 UCART2678 T	 UCART2878 T
6-11 5/8 (2124)	 UCART1684 T	 UCART1884 T	 UCART2084 T	 UCART2484 T	 UCART2684 T	 UCART2884 T
7-7 5/8 (2327)	 UCART1692 T	 UCART1892 T	 UCART2092 T	 UCART2492 T	 UCART2692 T	 UCART2892 T
7-11 5/8 (2429)	 UCART1696 T	 UCART1896 T	 UCART2096 T	 UCART2496 T	 UCART2696 T	 UCART2896 T

CASEMENT ROUND TOP

RT21 / RT22 TWO WIDE STANDARD SIZES - OPERATOR AND STATIONARY

RO (mm)	5-1 (1549)	5-5 (1651)	6-1 (1854)	6-9 (2057)
5-3 5/8 (1616)	 UCART3064 E	 UCART3264 E	 UCART3664 E	 UCART4064 E
5-11 5/8 (1819)	 UCART3072 T	 UCART3272 T	 UCART3672 T	 UCART4072 T
6-5 5/8 (1972)	 UCART3078 T	 UCART3278 T	 UCART3678 T	 UCART4078 T
6-11 5/8 (2124)	 UCART3084 T	 UCART3284 T	 UCART3684 T	 UCART4084 T
7-7 5/8 (2327)	 UCART3092 T	 UCART3292 T	 UCART3692 T	 UCART4092 T
7-11 5/8 (2429)	 UCART3096 T	 UCART3296 T	 UCART3696 T	

Details and Elevations not to scale.

- Marvin exclusive wash mode is not available on Ultimate Casement Round Tops.

E These windows meet national Egress codes for fire evacuation. Local codes may differ.

T For safety and/or code requirements, Marvin recommends tempered glass in all units with a frame size height of 71 1/8" or larger and units with basic frame size 25.2 ft².

Please consult your local Marvin representative for more information.

For further details and drawings visit the 'Tools and Documents' section at Marvin.com.

CASEMENT ROUND TOP

RT2 STANDARD SIZES OPERATOR AND STATIONARY

RO (mm)	2 - 1 (635)	2 - 3 (686)	2 - 5 (737)	2 - 7 (787)	2 - 9 (838)	3 - 1 (940)	3 - 5 (1041)
3 - 7 5/8 (1108)	 UCART2444						
3 - 11 5/8 (1210)	 UCART2448	 UCART2648					
4 - 5 5/8 (1362)	 UCART2454	 UCART2654	 UCART2854	 UCART3054			
4 - 7 5/8 (1413)	 UCART2456	 UCART2656	 UCART2856	 UCART3056 E	 UCART3256 E		
4 - 11 5/8 (1514)	 UCART2460	 UCART2660 E	 UCART2860 E	 UCART3060 E	 UCART3260 E		
5 - 3 5/8 (1616)	 UCART2464 E	 UCART2664 E	 UCART2864 E	 UCART3064 E	 UCART3264 E	 UCART3664 E	
5 - 11 5/8 (1819)	 UCART2472 T	 UCART2672 T	 UCART2872 T	 UCART3072 T	 UCART3272 T	 UCART3672 T	 UCART4072 T

CASEMENT ROUND TOP

RT2 STANDARD SIZES OPERATOR AND STATIONARY

RO (mm)	2 - 1 (635)	2 - 3 (686)	2 - 5 (737)	2 - 7 (787)	2 - 9 (838)	3 - 1 (940)	3 - 5 (1041)
6 - 5 5/8 (1972)	 UCART2478 T	 UCART2678 T	 UCART2878 T	 UCART3078 T	 UCART3278 T	 UCART3678 T	 UCART4078 T
6 - 11 5/8 (2124)	 UCART2484 T	 UCART2684 T	 UCART2884 T	 UCART3084 T	 UCART3284 T	 UCART3684 T	 UCART4084 T
7 - 7 5/8 (2327)	 UCART2492 T	 UCART2692 T	 UCART2892 T	 UCART3092 T	 UCART3292 T	 UCART3692 T	 UCART4092 T
7 - 11 5/8 (2429)	 UCART2496 T	 UCART2696 T	 UCART2896 T	 UCART3096 T	 UCART3296 T	 UCART3696 T	

Details and Elevations not to scale.
 T For safety and/or code requirements, Marvin recommends tempered glass in all units with a frame size height of 71 1/8" or larger and units with basic frame size 25.2 ft².
 Please consult your local Marvin representative for more information.
 For further details and drawings visit the 'Tools and Documents' section at Marvin.com.