

Casement Picture

MO (mm)	1' - 6" (457)	2' - 0" (610)	2' - 6" (762)	3' - 0" (914)	3' - 6" (1067)	4' - 0" (1219)	4' - 6" (1372)	5' - 0" (1524)	6' - 0" (1829)
RO (mm)	1' - 6" (457)	2' - 0" (610)	2' - 6" (762)	3' - 0" (914)	3' - 6" (1067)	4' - 0" (1219)	4' - 6" (1372)	5' - 0" (1524)	6' - 0" (1829)
FS (mm)	1' - 5 1/2" (445)	1' - 11 1/2" (597)	2' - 5 1/2" (749)	2' - 11 1/2" (902)	3' - 5 1/2" (1054)	3' - 11 1/2" (1207)	4' - 5 1/2" (1359)	4' - 11 1/2" (1511)	5' - 11 1/2" (1816)
DLO (mm)	11 53/64" (300)	17 53/64" (453)	23 53/64" (605)	29 53/64" (757)	35 53/64" (910)	41 53/64" (1062)	47 53/64" (1215)	53 53/64" (1367)	65 53/64" (1672)
1' - 11 3/4" (603) 2' - 0" (610) 2' - 5 3/4" (756) 2' - 6" (762) 2' - 11 3/4" (908) 3' - 0" (914) 3' - 5 3/4" (1060) 3' - 6" (1067) 3' - 11 3/4" (1213) 4' - 0" (1219) 4' - 5 3/4" (1365) 4' - 6" (1372) 4' - 11 3/4" (1518) 5' - 0" (1524) 5' - 5 3/4" (1670) 5' - 6" (1676) 5' - 11 3/4" (1822)									
1' - 11 1/2" (597) 2' - 5 1/2" (749) 2' - 6" (762) 2' - 11 1/2" (902) 3' - 0" (914) 3' - 5 1/2" (1054) 3' - 6" (1067) 3' - 11 1/2" (1207) 4' - 0" (1219) 4' - 5 1/2" (1359) 4' - 6" (1372) 4' - 11 1/2" (1511) 5' - 0" (1524) 5' - 5 1/2" (1664) 5' - 6" (1676) 5' - 11 1/2" (1816)									
2' - 5 3/4" (756) 2' - 6" (762) 2' - 11 3/4" (908) 3' - 0" (914) 3' - 5 3/4" (1060) 3' - 6" (1067) 3' - 11 3/4" (1213) 4' - 0" (1219) 4' - 5 3/4" (1365) 4' - 6" (1372) 4' - 11 3/4" (1518) 5' - 0" (1524) 5' - 5 3/4" (1670) 5' - 6" (1676) 5' - 11 3/4" (1822)									
2' - 11 1/2" (902) 2' - 5 1/2" (749) 2' - 6" (762) 2' - 11 3/4" (908) 3' - 0" (914) 3' - 5 1/2" (1054) 3' - 6" (1067) 3' - 11 3/4" (1213) 4' - 0" (1219) 4' - 5 1/2" (1359) 4' - 6" (1372) 4' - 11 1/2" (1511) 5' - 0" (1524) 5' - 5 1/2" (1664) 5' - 6" (1676) 5' - 11 1/2" (1816)									
2' - 5 3/4" (756) 2' - 6" (762) 2' - 11 3/4" (908) 3' - 0" (914) 3' - 5 3/4" (1060) 3' - 6" (1067) 3' - 11 3/4" (1213) 4' - 0" (1219) 4' - 5 3/4" (1365) 4' - 6" (1372) 4' - 11 3/4" (1518) 5' - 0" (1524) 5' - 5 3/4" (1670) 5' - 6" (1676) 5' - 11 3/4" (1822)									
2' - 11 1/2" (902) 2' - 5 1/2" (749) 2' - 6" (762) 2' - 11 3/4" (908) 3' - 0" (914) 3' - 5 1/2" (1054) 3' - 6" (1067) 3' - 11 3/4" (1213) 4' - 0" (1219) 4' - 5 1/2" (1359) 4' - 6" (1372) 4' - 11 1/2" (1511) 5' - 0" (1524) 5' - 5 1/2" (1664) 5' - 6" (1676) 5' - 11 1/2" (1816)									
2' - 5 3/4" (756) 2' - 6" (762) 2' - 11 3/4" (908) 3' - 0" (914) 3' - 5 3/4" (1060) 3' - 6" (1067) 3' - 11 3/4" (1213) 4' - 0" (1219) 4' - 5 3/4" (1365) 4' - 6" (1372) 4' - 11 3/4" (1518) 5' - 0" (1524) 5' - 5 3/4" (1670) 5' - 6" (1676) 5' - 11 3/4" (1822)									
2' - 11 1/2" (902) 2' - 5 1/2" (749) 2' - 6" (762) 2' - 11 3/4" (908) 3' - 0" (914) 3' - 5 1/2" (1054) 3' - 6" (1067) 3' - 11 3/4" (1213) 4' - 0" (1219) 4' - 5 1/2" (1359) 4' - 6" (1372) 4' - 11 1/2" (1511) 5' - 0" (1524) 5' - 5 1/2" (1664) 5' - 6" (1676) 5' - 11 1/2" (1816)									
2' - 5 3/4" (756) 2' - 6" (762) 2' - 11 3/4" (908) 3' - 0" (914) 3' - 5 3/4" (1060) 3' - 6" (1067) 3' - 11 3/4" (1213) 4' - 0" (1219) 4' - 5 3/4" (1365) 4' - 6" (1372) 4' - 11 3/4" (1518) 5' - 0" (1524) 5' - 5 3/4" (1670) 5' - 6" (1676) 5' - 11 3/4" (1822)									

Details and Elevations not to scale.

Special sized units available within product size matrix. See your Marvin retailer.














T = Standard Tempered.

GBG available in standard Rectangular lite cut, shown above. Other GBG lite cuts shown on page 5.

See page 58 for specific PG Ratings.

For further details and drawings visit the 'Technical Specifications' section at Marvin.com.

Casement Picture

MO (mm)	1' - 6" (457)	2' - 0" (610)	2' - 6" (762)	3' - 0" (914)	3' - 6" (1067)	4' - 0" (1219)	4' - 6" (1372)	5' - 0" (1524)	6' - 0" (1829)
RO (mm)	1' - 6" (457)	2' - 0" (610)	2' - 6" (762)	3' - 0" (914)	3' - 6" (1067)	4' - 0" (1219)	4' - 6" (1372)	5' - 0" (1524)	6' - 0" (1829)
FS (mm)	1' - 5 1/2" (445)	1' - 11 1/2" (597)	2' - 5 1/2" (749)	2' - 11 1/2" (902)	3' - 5 1/2" (1054)	3' - 11 1/2" (1207)	4' - 5 1/2" (1359)	4' - 11 1/2" (1511)	5' - 11 1/2" (1816)
DLO (mm)	11 53/64" (300)	17 53/64" (453)	23 53/64" (605)	29 53/64" (757)	35 53/64" (910)	41 53/64" (1062)	47 53/64" (1215)	53 53/64" (1367)	65 53/64" (1672)
6-5 3/4 (1975)									
6-6 (1981)									
6-5 1/2 (1969)									
71 53/64 (1824)									
									
									
									
									
									
6-11 3/4 (2127)									
7-0 (2134)									
6-11 1/2 (2121)									
77 53/64 (1977)									
									
									
									
									
									

Details and Elevations not to scale.

Special sized units available within product size matrix. See your Marvin retailer.

T = Standard Tempered.

GBG available on all sizes in standard Rectangular lite cut, shown above. Other GBG lite cuts shown on page 5.

See page 58 for specific PG Ratings.

For further details and drawings visit the 'Technical Specifications' section at Marvin.com.