







Inswing French Door G2

6-6R Height

MO (mm)	1-8 11/32 (517)	2-7 1/8 (791)	3-1 1/8 (943)	4-11 1/2 (1511)	5-11 1/2 (1816)	8-9 7/8 (2689)	7-10 11/16 (2405)
RO (mm)	1-8 27/32 (529)	2-7 5/8 (803)	3-1 5/8 (956)	5-0 (1524)	6-0 (1829)	8-10 3/8 (2702)	7-11 3/16 (2418)
FS (mm)	1-7 27/32 (504)	2-6 5/8 (778)	3-0 5/8 (930)	4-11 (1499)	5-11 (1803)	8-9 3/8 (2677)	7-10 3/16 (2392)
DLO (mm)	0-11 1/2 (292)	1-6 25/32 (477)	2-0 25/32 (629)	1-6 25/32 (477)	2-0 25/32 (629)	2-0 25/32 (629)	0-11 1/2 (292) 1-6 25/32 (477)

6-7 3/4 (2026) 6-8 (2032) 6-7 1/2 (2019) 5-3 47/64 (1794)							
	UIFDSL G2 1666	UIFDG2 26R66R	UIFDG2 30R66R	UIFDG2 50R66R	UIFDG2 60R66R	UIFDG2 90R66R	UIFDG2 80R66R SLXXSL

R = Retro Size

- All glass is tempered.
- 6 9/16" jambs required for Inswing French Door G2 and Inswing French Door 2 1/4" G2
- Doors above CN 8/0 height use 2 1/4" panels.
- Some configurations require KD.

Details and Elevations not to scale.

Please consult your local Marvin representative for additional mulling configurations.

Please consult your local Marvin representative for masonry openings that include casings and subsills.






For further details and drawings visit the 'Technical Specifications' section at Marvin.com.

ULTIMATE INSWING FRENCH DOOR G2: UIFDG2
ULTIMATE INSWING FRENCH DOOR 2 1/4" G2: UIFD225G2

Inswing French Door G2

1 Panel With

MO (mm)	1-8 11/32 (517)	2-1 15/16 (659)	2-7 15/16 (811)	2-9 15/16 (862)	3-1 15/16 (964)	3-7 15/16 (1116)
RO (mm)	1-8 27/32 (529)	2-2 7/16 (672)	2-8 7/16 (824)	2-10 7/16 (875)	3-2 7/16 (976)	3-8 7/16 (1129)
FS (mm)	1-7 27/32 (504)	2-1 7/16 (646)	2-7 7/16 (799)	2-9 7/16 (849)	3-1 7/16 (951)	3-7 7/16 (1103)
DLO (mm)	0-11 1/2 (292)	1-1 19/32 (345)	1-7 19/32 (498)	1-9 19/32 (548)	2-1 19/32 (650)	2-7 19/32 (802)

6-10 1/4 (2089) 6-10 1/2 (2096) 6-10 (2083) 5-6 15/64 (1858)	 UIFDG2 1668 UIFD2.25SLG2 1668	 UIFDG2 2068 UIFD2.25G2 2068	 UIFDG2 2668 UIFD2.25G2 2668	 UIFDG2 2868 UIFD2.25G2 2868	 UIFDG2 3068 UIFD2.25G2 3068	 UIFDG2 3668 UIFD2.25G2 3668
7-2 1/4 (2191) 7-2 1/2 (2197) 7-2 (2184) 5-10 15/64 (1959)	 UIFDG2 1670 UIFD2.25SLG2 1670	 UIFDG2 2070 UIFD2.25G2 2070	 UIFDG2 2670 UIFD2.25G2 2670	 UIFDG2 2870 UIFD2.25G2 2870	 UIFDG2 3070 UIFD2.25G2 3070	 UIFDG2 3670 UIFD2.25G2 3670
8-2 1/4 (2496) 8-2 1/2 (2502) 8-2 (2489) 6-10 15/64 (2264)	 UIFDG2 1680 UIFD2.25SLG2 1680	 UIFDG2 2080 UIFD2.25G2 2080	 UIFDG2 2680 UIFD2.25G2 2680	 UIFDG2 2880 UIFD2.25G2 2880	 UIFDG2 3080 UIFD2.25G2 3080	 UIFDG2 3680 UIFD2.25G2 3680
9-2 1/4 (2800) 9-2 1/2 (2807) 9-2 (2794) 7-10 15/64 (2569)	 UIFD2.25SLG2 1690	 UIFD2.25G2 2090	 UIFD2.25G2 2690	 UIFD2.25G2 2890	 UIFD2.25G2 3090	 UIFD2.25G2 3690
10-2 1/4 (3105) 10-2 1/2 (3112) 10-2 (3099) 8-10 15/64 (2874)	 UIFD2.25SLG2 16100	 UIFD2.25G2 20100	 UIFD2.25G2 26100	 UIFD2.25G2 28100	 UIFD2.25G2 30100	 UIFD2.25G2 36100

R = Retro Size

- All glass is tempered.
- 6 9/16" jambs required for Inswing French Door G2 and Inswing French Door 2 1/4" G2
- Doors above CN 8/0 height use 2 1/4" panels.
- Some configurations require KD.

Details and Elevations not to scale.

Please consult your local Marvin representative for additional mulling configurations.
















Please consult your local Marvin representative for masonry openings that include casings and subsills.

For further details and drawings visit the 'Technical Specifications' section at Marvin.com.

Inswing French Door G2

2 Panel Width

MO (mm)	4-1 1/8 (1248)	5-1 1/8 (1553)	5-5 1/8 (1654)	6-1 1/8 (1857)	7-1 1/8 (2162)
RO (mm)	4-1 5/8 (1260)	5-1 5/8 (1565)	5-5 5/8 (1667)	6-1 5/8 (1870)	7-1 5/8 (2175)
FS (mm)	4-0 5/8 (1235)	5-0 5/8 (1540)	5-4 5/8 (1641)	6-0 5/8 (1845)	7-0 5/8 (2149)
DLO (mm)	1-1 19/32 (345)	1-7 19/32 (498)	1-9 19/32 (548)	2-1 19/32 (650)	2-7 19/32 (802)

6-10 1/4 (2089) 6-10 1/2 (2096) 6-10 (2083) 5-6 15/64 (1858)	 UIFDG2 4068 UIFD2.25G2 4068	 UIFDG2 5068 UIFD2.25G2 5068	 UIFDG2 5468 UIFD2.25G2 5468	 UIFDG2 6068 UIFD2.25G2 6068	 UIFDG2 7068 UIFD2.25G2 7068
7-2 1/4 (2191) 7-2 1/2 (2197) 7-2 (2184) 5-10 15/64 (1959)	 UIFDG2 4070 UIFD2.25G2 4070	 UIFDG2 5070 UIFD2.25G2 5070	 UIFDG2 5470 UIFD2.25G2 5470	 UIFDG2 6070 UIFD2.25G2 6070	 UIFDG2 7070 UIFD2.25G2 7070
8-2 1/4 (2496) 8-2 1/2 (2502) 8-2 (2489) 6-10 15/64 (2264)	 UIFDG2 4080 UIFD2.25G2 4080	 UIFDG2 5080 UIFD2.25G2 5080	 UIFDG2 5480 UIFD2.25G2 5480	 UIFDG2 6080 UIFD2.25G2 6080	 UIFDG2 7080 UIFD2.25G2 7080
9-2 1/4 (2800) 9-2 1/2 (2807) 9-2 (2794) 7-10 15/64 (2569)	 UIFD2.25G2 4090	 UIFD2.25G2 5090	 UIFD2.25G2 5490	 UIFD2.25G2 6090	 UIFD2.25G2 7090
10-2 1/4 (3105) 10-2 1/2 (3112) 10-2 (3099) 8-10 15/64 (2874)	 UIFD2.25G2 40100	 UIFD2.25G2 50100	 UIFD2.25G2 54100	 UIFD2.25G2 60100	 UIFD2.25G2 70100

R = Retro Size

- All glass is tempered.
- 6 9/16" jambs required for Inswing French Door G2 and Inswing French Door 2 1/4" G2
- Doors above CN 8/0 height use 2 1/4" panels.
- Some configurations require KD.

Details and Elevations not to scale.

























Please consult your local Marvin representative for additional mulling configurations.

Please consult your local Marvin representative for masonry openings that include casings and subsills.

For further details and drawings visit the 'Technical Specifications' section at Marvin.com.

Inswing French Door G2

3 Panel With

MO (mm)	6-0 5/16 (1837)	7-6 5/16 (2294)	8-0 5/16 (2446)	9-0 5/16 (2751)	10-6 5/16 (3208)
RO (mm)	6-0 13/16 (1849)	7-6 13/16 (2307)	8-0 13/16 (2459)	9-0 13/16 (2764)	10-6 13/16 (3221)
FS (mm)	5-11 13/16 (1824)	7-5 13/16 (2281)	7-11 13/16 (2434)	8-11 13/16 (2738)	10-5 13/16 (3196)
DLO (mm)	1-1 19/32 (345)	1-7 19/32 (498)	1-9 19/32 (548)	2-1 19/32 (650)	2-7 19/32 (802)
6-10 1/4 (2089)					
6-10 1/2 (2096)	UIFDG2 6068 UIFD2.25G2 6068	UIFDG2 7668 UIFD2.25G2 7668	UIFDG2 8068 UIFD2.25G2 8068	UIFDG2 9068 UIFD2.25G2 9068	UIFDG2 10668 UIFD2.25G2 10668
6-10 (2083)					
5-6 15/64 (1858)					
7-2 1/4 (2191)					
7-2 1/2 (2197)	UIFDG2 6070 UIFD2.25G2 6070	UIFDG2 7670 UIFD2.25G2 7670	UIFDG2 8070 UIFD2.25G2 8070	UIFDG2 9070 UIFD2.25G2 9070	UIFDG2 10670 UIFD2.25G2 10670
7-2 (2184)					
5-10 15/64 (1959)					
8-2 1/4 (2496)					
8-2 1/2 (2502)	UIFDG2 6080 UIFD2.25G2 6080	UIFDG2 7680 UIFD2.25G2 7680	UIFDG2 8080 UIFD2.25G2 8080	UIFDG2 9080 UIFD2.25G2 9080	UIFDG2 10680 UIFD2.25G2 10680
8-2 (2489)					
6-10 15/64 (2264)					
9-2 1/4 (2800)					
9-2 1/2 (2807)	UIFD2.25G2 6090	UIFD2.25G2 7690	UIFD2.25G2 8090	UIFD2.25G2 9090	UIFD2.25G2 10690
9-2 (2794)					
7-10 15/64 (2569)					
10-2 1/4 (3105)					
10-2 1/2 (3112)	UIFD2.25G2 60100	UIFD2.25G2 76100	UIFD2.25G2 80100	UIFD2.25G2 90100	UIFD2.25G2 106100
10-2 (3099)					
8-10 15/64 (2874)					

R = Retro Size

- All glass is tempered.
- 6 9/16" jambs required for Inswing French Door G2 and Inswing French Door 2 1/4" G2
- Doors above CN 8/0 height use 2 1/4" panels.
- Some configurations require KD.

Details and Elevations not to scale.





















Please consult your local Marvin representative for additional mulling configurations.

Please consult your local Marvin representative for masonry openings that include casings and subsills.

For further details and drawings visit the 'Technical Specifications' section at Marvin.com.

Inswing French Door G2

4 Panel Width

MO (mm)	7-11 1/2 (2426)	9-11 1/2 (3035)	10-7 1/2 (3239)	11-11 1/2 (3645)
RO (mm)	8-0 (2438)	10-0 (3048)	10-8 (3251)	12-0 (3658)
FS (mm)	7-11 (2413)	9-11 (3023)	10-7 (3226)	11-11 (3632)
DLO (mm)	1-1 19/32 (345)	1-7 19/32 (498)	1-9 19/32 (548)	2-1 19/32 (650)
6-10 1/4 (2089)				
6-10 1/2 (2096)	UIFDG2 8068 UIFD2.25G2 8068	UIFDG2 10068 UIFD2.25G2 10068	UIFDG2 10868 UIFD2.25G2 10868	UIFDG2 12068 UIFD2.25G2 12068
6-10 (2083)				
5-6 15/64 (1858)				
7-2 1/4 (2191)				
6-10 1/2 (2096)	UIFDG2 8070 UIFD2.25G2 8070	UIFDG2 10070 UIFD2.25G2 10070	UIFDG2 10870 UIFD2.25G2 10870	UIFDG2 12070 UIFD2.25G2 12070
7-2 1/2 (2197)				
7-2 (2184)				
5-10 15/64 (1959)				
8-2 1/4 (2496)				
8-2 1/2 (2502)	UIFDG2 8080 UIFD2.25G2 8080	UIFDG2 10080 UIFD2.25G2 10080	UIFDG2 10880 UIFD2.25G2 10880	UIFDG2 12080 UIFD2.25G2 10880
8-2 (2489)				
6-10 15/64 (2264)				
9-2 1/4 (2800)				
9-2 1/2 (2807)	UIFD2.25G2 8090	UIFD2.25G2 10090	UIFD2.25G2 10890	UIFD2.25G2 12090
9-2 (2794)				
7-10 15/64 (2569)				
10-2 1/4 (3105)				
10-2 1/2 (3112)	UIFD2.25G2 80100	UIFD2.25G2 100100	UIFD2.25G2 108100	UIFD2.25G2 120100
10-2 (3099)				
8-10 15/64 (2874)				

R = Retro Size

- All glass is tempered.
- 6 9/16" jambs required for Inswing French Door G2 and Inswing French Door 2 1/4" G2
- Doors above CN 8/0 height use 2 1/4" panels.
- Some configurations require KD.

Details and Elevations not to scale.

Please consult your local Marvin representative for additional mulling configurations.

Please consult your local Marvin representative for masonry openings that include casings and subsills.


For further details and drawings visit the 'Technical Specifications' section at Marvin.com.

Inswing French Door G2

4 Panel With


MO (mm)	13-11 1/2 (4255)
RO (mm)	14-0 (4267)
FS (mm)	13-11 (4242)
DLO (mm)	2-7 19/32 (802)

6-10 1/4 (2089)				
6-10 1/2 (2096)				
6-10 (2083)				
5-6 15/64 (1858)				




UIFDG2 14068
UIFD2.25G2 14068

7-2 1/4 (2191)				
7-2 1/2 (2197)				
7-2 (2184)				
5-10 15/64 (1959)				




UIFDG2 14070
UIFD2.25G2 14070

8-2 1/4 (2496)				
8-2 1/2 (2502)				
8-2 (2489)				
6-10 15/64 (2264)				




UIFDG2 14080
UIFD2.25G2 14080

9-2 1/4 (2800)				
9-2 1/2 (2807)				
9-2 (2794)				
7-10 15/64 (2569)				



UIFD2.25G2 14090

10-2 1/4 (3105)				
10-2 1/2 (3112)				
10-2 (3099)				
8-10 15/64 (2874)				



UIFD2.25G2 140100

R = Retro Size

- All glass is tempered.
- 6 9/16" jambs required for Inswing French Door G2 and Inswing French Door 2 1/4" G2
- Doors above CN 8/0 height use 2 1/4" panels.
- Some configurations require KD.

Details and Elevations not to scale.

Please consult your local Marvin representative for additional mulling configurations.

Please consult your local Marvin representative for masonry openings that include casings and subsills.

For further details and drawings visit the 'Technical Specifications' section at Marvin.com.